

**ADVANCE EUROPEAN** 



STYLISH TWIN PROJECTOR WITH DRL & LED LAMPS


























Engine Engine HP (Category) 55   No. of Cylinders 3   Rated RPM 2000   Displacement (cc) 3067   Max Torque (Nm) 205   Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission   Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
No. of Cylinders 3   Rated RPM 2000   Displacement (cc) 3067   Max Torque (Nm) 205   Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission   Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO Standard RPM   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Rated RPM 2000   Displacement (cc) 3067   Max Torque (Nm) 205   Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission   Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Displacement (cc) 3067   Max Torque (Nm) 205   Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission   Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Type Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Max Torque (Nm) 205   Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission   Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Type Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO   PTO Potendard RPM   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Air Cleaner Dry Air Cleaner With Clogging Sensor   Transmission Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake Brake Type Oil Immersed Brake   Hydraulics Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Transmission Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Type Oil Immersed Brake   Hydraulics 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Clutch Type Dual Clutch   Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake   Brake Type Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Gear Box 8F+2R   Max Speed (kmph) 33.4   Brake Brake Type Oil Immersed Brake   Hydraulics Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Brake Oil Immersed Brake   Brake Type Oil Immersed Brake   Hydraulics I800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Brake   Brake Type Oil Immersed Brake   Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO Prostandard RPM   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Brake Type Oil Immersed Brake   Hydraulics 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Hydraulics   Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO Power   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Lift Capacity (kg) 1800 Kg   3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO Prostandard RPM   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
3 Point Linkage CAT II   Hydraulic Control ADDC   Steering Power   PTO PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Hydraulic Control ADDC   Steering Power   PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Steering Power   PTO 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Steering Power   PTO 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
PTO 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
PTO Standard RPM 540   MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
MSR PTO Optional   Tyre 2WD 4WD   Front 7.5*16 9.5*24
Tyre 2WD 4WD   Front 7.5*16 9.5*24
Front 7.5*16 9.5*24
Tyre
Rear 16.9*28 16.9*28
Fuel Tank
Capacity (L) 55
Dimensions & Weight
Total Weight (kg) 2250-2380
Wheel Base (mm) 2074
Length (mm) 3885
Width (mm) 1850-1900
Front ballast weight 4x29 Kg





- E3 Engine having Xtra Power, Xtra Torque and Xtra Pickup.
- Efficient Fuel Combustion which results in extra mileage, extra engine life for trouble free operations
- High Engine Torque of 205 Nm
- Easy Super Synchro 8F+2R Gearbox for "Gear Shift on the Go"
- Max Speed of 33.4 Kmph for better productivity
- Optimized speed for better productivity in Rotavator
- Maintenance free transmission which saves time and money
- Tough transmission for Tough Haulage



**Next Generation Transmission** 



- Most Efficient braking in Tough Haulage
- Provides Longer Brakes Life due to multiple Discs
- Super Strong Brakes provides safety in hills
- Offers Highest PTO Power which gives better pulverization, Achieves 540 in 1680 ERPM which results in fuel saving
- Optional reverse PTO ensures dechoking of Rotavator, ensures easy operations and saves time



**PTO** 



- Prevents tractors from Front lifting
- Provides better stability in hilly roads
- Provides better control and Safe operations in hilly regions





Pembe Plaza Ground Floor, HomaBay Road Roundabout, Enterprise Road, P O Box 60275, 00100 Nairobi sales@sicheyautomotive.com | Hotline: +254 735 500 500, +254 780 465 797, +254 722 720 447

Dealership stamp